# **CLINIQON HC**



LEADING INNOVATIONS



**Delivery Bed**GRACE MOTHER CARE E

### **GRACE MOTHER CARE E**



#### PRODUCT FEATURES

Electrically operated Trendelenburg, reverse Trendelenburg position

Bed extension kit.

Adjustable and removeable PU legs support

Stainless steel side supports

Stainless steel removeable container for disposables

Cross lockable castors.

Central and directional lockable castors. (Optional)

Electrostatic painted metal frame.

Electronic thermal spray metal frame (Optional).

Easy cleanable, water resistant anti microbial upholstery.

Height adjustable stainless-steel IV pole.

Battery Backup. (Optional)

IPX4 standard electronic system.

Electrical operated backrest and height adjustment.

### TECHNICAL SPECIFICATIONS

**Overall Length Overall** 

**Overall Width** 

Height

Trendelenburg

**Reverse Trendelenburg** 

Backrest Angle (Max.)

**Castor Diameter** 

**Under Bed Clearance** 

Safe Working Load (With Accessories)

Power In

**Electrical Shock Protection** 

**Liquid Ingress Protection** 

**Batteries** 

222 cm

82 cm

51-82 cm

10°

10°

70°

2,5 cm

15 cm

200 Kg

1.5 Amax. 230VAC 50-60 Hz

Class I, Type B

IPX4 - IPX6

2x 12V Series, Connected,

Sealed, Rechargeable.











Backrest



High/Low



Trendelenburg



ReverseTrendelenburg





Electrically operated backrest and height adjustment.

Profile frame with easily removable ABS plastic covers.

Adjustable and removeable PU leg support

Stainless steel side supports

Stainless steel removeable container for disposables

Cross lockable castors.

Central and directional lockable castors. (Optional)

Electrostatic painted metal frame.

Electronic thermal spray metal frame (Optional).

Easy cleanable, water resistant anti microbial upholstery.

Height adjustable stainless-steel IV pole.

Battery Backup. (Optional)

IPX4 standard electronic system.

## TECHNICAL SPECIFICATIONS

**Overall Length** 

**Overall Width** 

Height Range

**Bed Surface Length** 

Backrest Angle (Max.)

**Castor Diameter** 

**Under Bed Clearance** 

Safe Working Load (With Accessories)

Power In

**Electrical Shock Protection** 

**Liquid Ingress Protection** 

188 cm

73 cm

59-91 cm

185 cm

67°

12,5 cm

15 cm

200 kg

1.5 Amax. 230VAC 50-60 Hz

Class I, Type B

IPX4 - IPX6

















